

2:1 Shrink Ratio, High Voltage, Very Flexible, V-0 Flammability, EV Tubing

DUNBAR-EV2500 is a flexible, flame retardant (V-0), heat shrinkable Modified Polyolefin tube for applications requiring outstanding high voltage and V-0 flammability standards. It reliably protects wires, solder joints, terminals, connections, and components.



PRODUCT FEATURES:

- Shrink ratio: 50% or more in the radial direction, 5% or less in the axial direction
- Operating Voltage (Max) 2.5 kV
- Continuous operating temperature: -55 °C (-67 °F) to +135 °C (+275 °F)
- Flammability: UL V-0
- Very Flexible
- Min. Shrink Temp 70 °C
- Standard Color EV Orange

Specification Values

Property		Test Standard	Value	
Physical	Unaged	Tensile Strength	Min. 1,500 psi	
		Elongation	Min. 200%	
	Aged	Tensile Strength	UL 224 158 °C x 168 hrs	
		Elongation	Min. 100%	
	Heat Shock		UL 224	No cracks, flowing or dripping
Cold Bend		-30 °C x 1 hr	No cracking	
Electrical	Dielectric Withstand	300 V	1500 V 1 min	Without breakdown
		600 V	2500 V 1 min	Without breakdown
	Dielectric Strength		UL 224	15 kV/mm min.
	Volume Resistivity		UL 224	Min. 10 ¹⁴ Ω · cm
Chemical	Copper Stability		158 °C x 168 hrs	No corrosion
	Anti Corrosion		UL 224	Pass
	Flammability		UL 94	V-0

Rev. December 2023


MATRIX PRECISION CONVERTING

Your Application. Our Expertise.

Matrix specializes in precision cutting and converting of engineered materials to meet the exact specifications required by manufacturers. Our state-of-the-art equipment and expertise ensure precise customization, providing manufacturers with streamlined solutions to enhance their product quality and performance.

DUNBAR – EV2500

2:1 SHRINK RATIO, HIGH VOLTAGE, VERY FLEXIBLE, V-0 FLAMMABILITY, EV TUBING



Product Dimensions

Minimum Shrink Temperature: 70 °C

Size	Expanded		Recovered			
	Internal Diameter (Minimum) (D)		Internal Diameter (Maximum) (d)		Wall Thickness (Minimum) (t)	
	in	mm	in	mm	in	mm
mm						
10/5	0.394	10.0	0.177	4.5	0.025	0.64
12.7/6.4	0.500	12.7	0.252	6.4	0.025	0.64
20/9.5	0.787	20.0	0.374	9.5	0.030	0.76
26/12.7	1.024	26.0	0.500	12.7	0.035	0.88
40/19	1.575	40.0	0.748	19.0	0.040	1.01
50/25	1.969	50.0	0.984	25.0	0.045	1.14

Rev. December 2023

Standard Colors: Orange
 Optional Color(s): Available by special order